



## PRODUCT DESCRIPTION

CSD is a neoprene based closed cell foam with a soft durometer. It has excellent oil, flame and weather-resistance. For customer convenience, it is available with pressure sensitive adhesive in custom die-cut form, upon request.

## TYPICAL APPLICATIONS

- Trucks, buses, construction, mining, agriculture, military transport, and emergency vehicles

## PRODUCT CONFIGURATIONS

- Available in 42" x 72" sheets
- 1/16" to 1 1/2" thick

## MARKETS



## PHYSICAL PROPERTIES

<b>Material Type</b>	Neoprene based closed cell foam
<b>Color</b>	Black
<b>Density</b>	11±3 lb/ft <sup>3</sup>
<b>Operating Temperature</b>	-40°C (-40°F) to 93°C (200°F)
<b>Tensile Strength</b>	60 PSI Min
<b>Elongation</b>	150%
<b>Compression Set</b>	20%
<b>Thermal Conductivity</b>	0.27 BTU in./h ft <sup>2</sup> °F
<b>Flame Resistance</b>	25.853(b) UL94 V0

## THE SOUNDSCOAT PROMISE

We have one goal: to enhance the customer experience by providing world-class products manufactured under ISO 9001:2015 and AS9100:2016 standards in one of our modern manufacturing facilities strategically located on each coast.

All materials are tested and qualified in our acoustics and materials testing laboratory to ensure consistent quality and performance.

Soundcoat products are supplied, tested, and produced to your specifications.

Visit [soundcoat.com](https://www.soundcoat.com) to see our complete line of absorption, barrier, damping, sealing, and thermal materials.

For further information on meeting specific requirements and for optimum product configuration, contact our Customer Service Group at 1-800-394-8913.

Rev. date 10/3/2025

The information contained herein is based on laboratory test data developed by or for Soundcoat and is believed to be reliable, but its accuracy or completeness is not guaranteed. The buyer must test this product to determine its suitability for his/her specific application before use. Only use a Soundcoat product after thoroughly consulting instructions on the data sheet for the specific product. SOUNDSCOAT DISCLAIMS ANY RESPONSIBILITY FOR 1) WARRANTIES OF FITNESS AND PURPOSE, 2) VERBAL RECOMMENDATIONS, 3) CONSEQUENTIAL DAMAGES FROM USE, AND 4) VIOLATION OF ANY PATENTS OR TRADEMARKS HELD BY OTHERS.

Kapton®, Nomex® and Tedlar® are registered trade names of Dupont Corporation.