

DAMPING PRODUCTS FOR THERMAL-ACOUSTIC SOLUTIONS

The Soundcoat portfolio of extensional and constrained damping products are engineered to stop structure-borne noise from impact sources, panel resonance, and radiated sound from structures.



THERMAL-ACOUSTIC DAMPING PORTFOLIO

Our portfolio of damping products is diverse to meet the needs of many different industries and applications. The Soundcoat technical support department can provide recommendations on proper material combinations based on your specific application. *Specific product details available via individual Technical Data Sheets. See all products listed on next page.*



GPDS - General Purpose Damping Sheet
(Filled plasticized PVC)



DYAD
(Polyurethane elastomer)

CUSTOMIZABLE PRODUCT CONFIGURATIONS

Soundcoat is more than just a damping material supplier; we can provide fully customized converting solutions. All damping materials are available various composite creations and with or without high performance pressure sensitive adhesive for ease of installation.

THE SOUNDCOAT PROMISE

We have one goal: to enhance the customer experience by providing world-class products manufactured under ISO 9001: 2015 and AS9100:2016 standards in one of our modern manufacturing facilities strategically located on each coast.

All materials are tested and qualified in our acoustics and materials testing laboratory to ensure consistent quality and performance.

Soundcoat products are supplied, tested, and produced to your specifications.

ISO 9001:2015 registered



ITAR compliant



AS9100:2016 registered

PPAP



Clean room manufacturing



FAI

TYPICAL MARKET APPLICATIONS

	DYAD	GPDS	Soundfoil LT	Soundfoil RT
Aerospace	X		X	
Aviation	X		X	
Trucks	X	X		X
Buses	X	X		X
Off-Highway & Specialty	X	X		X
Automation Equipment		X		X
Compressed Air		X		X
HVAC OEM		X		X
Off-Grid Power Gen		X		X
Data Centers		X		X
Semiconductor OEM		X		X
Energy Storage & Charging		X		X
Commercial Construction		X		X
Medical OEM & Devices	X	X		

Visit [soundcoat.com](https://www.soundcoat.com) to see our complete line of absorption, barrier, damping, sealing, and thermal materials, and to download specific product technical data sheets.

For further information on meeting specific requirements and for optimum product configuration, contact our Technical Support Department at 1-800-394-8913.

The information contained herein is based on laboratory test data developed by or for Soundcoat and is believed to be reliable, but its accuracy or completeness is not guaranteed. The buyer must test products to determine suitability for specific application before use. Only use a Soundcoat product after thoroughly consulting instructions on the data sheet for the specific product. SOUNDSCOAT DISCLAIMS ANY RESPONSIBILITY FOR 1) WARRANTIES OF FITNESS AND PURPOSE, 2) VERBAL RECOMMENDATIONS, 3) CONSEQUENTIAL DAMAGES FROM USE, AND 4) VIOLATION OF ANY PATENTS OR TRADEMARKS HELD BY OTHERS.